



## Technical Data



Input voltage	230 V AC
Nominal current	0.22
Running speed	9
IP code	IP55
Switch on duration	20

## MOUNTING POSITIONS



## TECHNICAL DATA

Matchcode	EA-SZ 230/65/750
Article name	Rack and pinion actuator EA-SZ 230/65/750
Part number	M2 1082 A
Input voltage	230 V AC
Nominal current	0.22
Stroke	750
Push force	650
Pull force	650
Cut-Off	integrated electronic overload cut-off
Running speed	9
IP code	IP55
Switch on duration	20
Mounting way	aufgesetzt
Weight	2.9
Housing	Rack housing: anodized aluminum E6 / EV1, gray motor housing: plastic, stroke + 220 mm x 54 x 120 mm
Housing type	Aluminium
Colour	On request
Housing length	220
Housing width	54
Housing height	120
Connection cable	Silicone cable 4 x 0.75 mm <sup>2</sup> , white, Length 1,500 mm

---

Nominal working temperature	20
Environment temperature range	-10 °C - 60 °C
Brackets included	ja

**ACCESSORIES**

Part no.	Matchcode	
<a href="#">M2 1083</a>	<a href="#">EA-SZ-M-350</a>	
<a href="#">M2 1083 A</a>	<a href="#">EA-SZ-VERBIND-1</a>	
<a href="#">M2 1083 B</a>	<a href="#">EA-SZ-VERBIND-2</a>	
<a href="#">M2 1084</a>	<a href="#">EA-SZ-M-550</a>	
<a href="#">M2 1089</a>	<a href="#">EA-SZ-M-750</a>	
<a href="#">M2 1091</a>	<a href="#">EA-SZ-M-1000</a>	