



Technical Data



Input voltage	230 V AC
Output voltage	24 V DC
Output current	48

TECHNICAL DATA

Matchcode	M-SHEV-48
Article name	Modular control panel M-SHEV-48
Part number	ST4 3449
Input voltage	230 V AC
Output voltage	24 V DC
Output current	48
Classification	CE certified EN 12101-10, tested ISO 21927-9
LED signs	LEDs on the loading card: 1. green LED "AKKU" = OK (Akku exists and is loading) 2. green LED "NETZ" = mains operation further LEDs on the modules
IP code	IP66
Housing	sheet steel case
Housing type	Steel case
Colour	RAL 7035
Housing width	600
Housing height	600
Housing depth	250
Appliance class	I
Environment temperature range	-5°C - +40°C

ACCESSORIES

Part no.	Matchcode
ST4 10120	Pb-battery-7Ah
ST4 10121	pb-battery-12ah
ST4 10122	pb-battery-17ah
ST4 10123	pb-battery-24ah
ST4 10124	Pb battery 38 Ah
ST4 3321	Flange plate 445-130 plastic
ST4 3322	Flange plate 345-130 plastic
ST4 3323	Flange plate 545-130 plastic
ST4 3344	HR-820-MS
ST4 3361	Charge electronics, type LB-120

ST4 3362	Charge electronics, type LB-140
ST4 3363	Charge electronics, type LB-160
ST4 3369	Charge electronics, type LB-120-10
ST4 3380	ZI-100
ST4 3381	SI-100
ST4 3382	MI-100
ST4 3383	MR-120
ST4 3385	MI-100-MB
ST4 3386	SI-100-MASTER
ST4 3389	BI-100-KNX