modul control panel M-SHEV-72



Technical Data

Input voltage	230 V AC
Output voltage	24 V DC
Output current	72

TECHNICAL DATA

Matchcode	M-SHEV-72
Article name	modul control panel M-SHEV-72
Part number	ST4 3451
Input voltage	230 V AC
Output voltage	24 V DC
Output current	72
Classification	CE certified EN 12101-10, tested ISO 21927-9
LED signs	LED display operating status network: Permanent display green - mains available LED display operating status lead acid battery ("O.K."): Continuous green - battery is present and charging (charge is being maintained)
IP code	IP66
Housing	Sheet steel case
Housing type	Steel case
Colour	RAL7035
Housing width	800
Housing height	800
Housing depth	250
Appliance class	I
Environment temperature range	-5°C - +40°C
Packaging part no.	N-98-021

ACCESSORIES

Part no.	Matchcode
ST4 10120	Pb-battery-7Ah
ST4 10121	pb-battery-12ah
ST4 10122	pb-battery-17ah
ST4 10123	pb-battery-24ah
ST4 10124	Pb battery 38 Ah
ST4 3321	Flange plate 445-130 plastic
ST4 3322	Flange plate 345-130 plastic
ST4 3323	Flange plate 545-130 plastic

modul control panel M-SHEV-72

ST4 3344	HR-820-MS
ST4 3380	ZI-100
ST4 3381	SI-100
ST4 3382	MI-100
ST4 3383	MR-120
ST4 3385	BI-100-MB
ST4 3386	SI-100-MASTER
ST4 3389	BI-100-KNX