



**Technical Data**



Input voltage	230 V AC
Output voltage	24 V DC
Output current	72

**TECHNICAL DATA**

Matchcode	M-SHEV-72
Article name	modul control panel M-SHEV-72
Part number	ST4 3451
Input voltage	230 V AC
Output voltage	24 V DC
Output current	72
Classification	CE certified EN 12101-10, tested ISO 21927-9
LED signs	LED display operating status network: Permanent display green - mains available LED display operating status lead acid battery ("O.K."): Continuous green - battery is present and charging (charge is being maintained)
IP code	IP66
Housing	Sheet steel case
Housing type	Steel case
Colour	RAL7035
Housing width	800
Housing height	800
Housing depth	250
Appliance class	I
Environment temperature range	-5°C - +40°C

**ACCESSORIES**

Part no.	Matchcode
<a href="#">ST4 10120</a>	<a href="#">Pb-battery-7Ah</a>
<a href="#">ST4 10121</a>	<a href="#">pb-battery-12ah</a>
<a href="#">ST4 10122</a>	<a href="#">pb-battery-17ah</a>
<a href="#">ST4 10123</a>	<a href="#">pb-battery-24ah</a>
<a href="#">ST4 10124</a>	<a href="#">Pb battery 38 Ah</a>
<a href="#">ST4 3321</a>	<a href="#">Flange plate 445-130 plastic</a>
<a href="#">ST4 3322</a>	<a href="#">Flange plate 345-130 plastic</a>
<a href="#">ST4 3323</a>	<a href="#">Flange plate 545-130 plastic</a>
<a href="#">ST4 3344</a>	<a href="#">HR-820-MS</a>

<a href="#">ST4 3361</a>	<a href="#">Charge electronics, type LB-120</a>
<a href="#">ST4 3362</a>	<a href="#">Charge electronics, type LB-140</a>
<a href="#">ST4 3363</a>	<a href="#">Charge electronics, type LB-160</a>
<a href="#">ST4 3369</a>	<a href="#">Charge electronics, type LB-120-10</a>
<a href="#">ST4 3380</a>	<a href="#">ZI-100</a>
<a href="#">ST4 3381</a>	<a href="#">SI-100</a>
<a href="#">ST4 3382</a>	<a href="#">MI-100</a>
<a href="#">ST4 3383</a>	<a href="#">MR-120</a>
<a href="#">ST4 3385</a>	<a href="#">MI-100-MB</a>
<a href="#">ST4 3386</a>	<a href="#">SI-100-MASTER</a>
<a href="#">ST4 3389</a>	<a href="#">BI-100-KNX</a>