



## Technical Data



Input voltage	230 V AC
Output voltage	24 V DC
Output current	12

## TECHNICAL DATA

Matchcode	M-SHEV-12-S
Article name	Modular control panel M-SHEV-12-S
Part number	ST4 3446
Input voltage	230 V AC
Output voltage	24 V DC
Output current	12
Classification	CE certified EN 12101-10, tested ISO 21927-9
LED signs	LEDs on load cards: 1. green LED "AKKU" = OK (Akku exists and is loading) 2. green LED "NETZ" = mains operation further LEDs on the modules
IP code	IP66
Housing	sheet steel case, different housing sizes
Housing type	Steel case
Colour	RAL 7035
Appliance class	I
Environment temperature range	-5°C - +40°C

## ACCESSORIES

Part no.	Matchcode	
<a href="#">ST4 10120</a>	<a href="#">Pb-battery-7Ah</a>	
<a href="#">ST4 10121</a>	<a href="#">pb-battery-12ah</a>	
<a href="#">ST4 10122</a>	<a href="#">pb-battery-17ah</a>	
<a href="#">ST4 10123</a>	<a href="#">pb-battery-24ah</a>	
<a href="#">ST4 10124</a>	<a href="#">Pb battery 38 Ah</a>	
<a href="#">ST4 3321</a>	<a href="#">Flange plate 445-130 plastic</a>	
<a href="#">ST4 3322</a>	<a href="#">Flange plate 345-130 plastic</a>	
<a href="#">ST4 3323</a>	<a href="#">Flange plate 545-130 plastic</a>	
<a href="#">ST4 3344</a>	<a href="#">HR-820-MS</a>	
<a href="#">ST4 3361</a>	<a href="#">Charge electronics, type LB-120</a>	
<a href="#">ST4 3362</a>	<a href="#">Charge electronics, type LB-140</a>	
<a href="#">ST4 3363</a>	<a href="#">Charge electronics, type LB-160</a>	
<a href="#">ST4 3369</a>	<a href="#">Charge electronics, type LB-120-10</a>	

<a href="#">ST4 3380</a>	<a href="#">ZI-100</a>
<a href="#">ST4 3381</a>	<a href="#">SI-100</a>
<a href="#">ST4 3382</a>	<a href="#">MI-100</a>
<a href="#">ST4 3383</a>	<a href="#">MR-120</a>
<a href="#">ST4 3385</a>	<a href="#">MI-100-MB</a>
<a href="#">ST4 3386</a>	<a href="#">SI-100-MASTER</a>
<a href="#">ST4 3389</a>	<a href="#">BI-100-KNX</a>