



Technical Data



Input voltage	230 V AC
Output voltage	24 V DC
Output current	72

TECHNICAL DATA

Matchcode	M-SHEV-72-S
Article name	Modular control panel M-SHEV-72-S
Part number	ST4 3452
Input voltage	230 V AC
Output voltage	24 V DC
Output current	72
Classification	CE certified EN 12101-10, tested ISO 21927-9
LED signs	LEDs on load cards: 1. green LED "AKKU" = OK (Akku exists and is loading) 2. green LED "NETZ" = mains operation further LEDs on the modules
IP code	IP66
Housing	sheet steel case, different housing sizes
Housing type	Steel case
Colour	RAL 7035
Appliance class	I
Environment temperature range	-5°C - +40°C

ACCESSORIES

Part no.	Matchcode	
ST4 10120	Pb-battery-7Ah	
ST4 10121	pb-battery-12ah	
ST4 10122	pb-battery-17ah	
ST4 10123	pb-battery-24ah	
ST4 10124	Pb battery 38 Ah	
ST4 3321	Flange plate 445-130 plastic	
ST4 3322	Flange plate 345-130 plastic	
ST4 3323	Flange plate 545-130 plastic	
ST4 3344	HR-820-MS	
ST4 3361	Charge electronics, type LB-120	
ST4 3362	Charge electronics, type LB-140	
ST4 3363	Charge electronics, type LB-160	
ST4 3369	Charge electronics, type LB-120-10	

ST4 3380	ZI-100
ST4 3381	SI-100
ST4 3382	MI-100
ST4 3383	MR-120
ST4 3385	MI-100-MB
ST4 3386	SI-100-MASTER
ST4 3389	BI-100-KNX