




Technical Data



Input voltage	230 V AC
Nominal current	0.23
Running speed	9.7
IP code	IP32
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	EA230-K-30/1000
Article name	chain actuator EA230-K-30/1000
Part number	M2 5143
Input voltage	230 V AC
Nominal current	0.23
Input voltage range	- 10 % / + 10 %
Stroke	1000
Push force	300
Pull force	300
Nominal locking force	2000
Cut-Off	Integrated electronic overload cut-off
Running speed	9.7
IP code	IP32
Switch on duration	30
Mounting way	aufgesetzt
Weight	2.2
Housing	Aluminium profile housing E6/EV1 anodized
Housing type	Aluminium
Colour	On request
Housing length	824
Housing width	35
Housing height	37
Appliance class	III
Connection cable	plastic connection cable 3 x 0.5 mm ² , white, length 2,000 mm
Nominal working temperature	20
Environment temperature range	0 °C - 75 °C
Brackets included	nein

ACCESSORIES

Part no.	Matchcode
K2 5089	K-K50-OK
K2 5097	K-K30-A
K2 5098	K-K30-K
K2 5104	K-K30-FLEX
K2 5105	K-K30-AKI
K2 5106	K-K-OK-SK
K2 5107	K-K30-ZB
K2 5108	K-K30-AKI-R