



## Technical Data



### TECHNICAL DATA

Matchcode	RSV-180-XL
Article name	Smoke curtain system Smoke PROtec RSV-180-XL
Part number	RSV 52020
Classification	EN 12101-1, ASB 3, D120 (fail-safe) 120 minutes at 600 Å°C
Fabric	One-side PU-coated glass fabric 590 g/m2, colour: grey, non-inflammable according to DIN 4102-1, A2, smoke-proof tested according to the test procedures in accordance with DIN EN 1634-3. descending by gravity (gravity fail safe)
Unwind	planet drive, 24 V DC, 3 A with electric load breaking; maximum turning moment 4 Nm, roll shaft-integrated.
Rewind	
System installation	Ceiling or wall mounted with appropriate approved mounting material
System size	max. 6 x 3 m (WxH)
Housing	Galvanized sheet steel 1 mm powder-coated RAL 7035; Single roller 150 x 180 mm
Bottom Bar	Sheet steel 1 mm powder-coated RAL 7035 with integrated round steel in fabric bag for energy free dropping
Housing type	Steel case
Colour	RAL 7035

### ACCESSORIES

Part no.	Matchcode
<a href="#">A3 2064</a>	<a href="#">RM 3000 FSV</a>
<a href="#">A3 2178</a>	<a href="#">HE 087 Yellow FSV</a>
<a href="#">M2 3330</a>	<a href="#">AM-830</a>
<a href="#">ST4 3170</a>	<a href="#">SHEV 3 RSV</a>
<a href="#">ST4 3171</a>	<a href="#">SHEV 6 RSV</a>
<a href="#">ST4 3422</a>	<a href="#">M-SHEV-24-RSV</a>
<a href="#">ST4 3423</a>	<a href="#">M-SHEV-12-RSV</a>