



**Technical Data**



**TECHNICAL DATA**

Matchcode	FIRESCREEN-225-SFS-EW
Article name	Fire Curtain FIRESCREEN-225-SFS-EW
Part number	FSV 54100
Classification	E120 EW90 C2 according EN 13501-2 CE according EN 16034
Fabric	Polyurethane coated Fabric, 8 mm thick
Unwind	Through Gravity (gravity fail safe)
Rewind	Through integrated tube motor 230 V AC - end limits can be adjusted
System installation	Ceiling or wall mounting with appropriate and verified material
System size	max. 4000 x 3000 mm (WxH)
Housing	Headbox: 225 x 225 mm (WxH); Side guides: 120 x 65 mm; Galvanized sheet steel
Bottom Bar	Round bar as weight inside of the fabric
Housing type	Steel case

**ACCESSORIES**

Part no.	Matchcode
<a href="#">A3 2054</a>	<a href="#">RM 2860 FSV</a>
<a href="#">A3 2167</a>	<a href="#">HE-088-YELLOW-ALU</a>
<a href="#">A3 2168</a>	<a href="#">HE-088-ORANGE-ALU</a>
<a href="#">ST4 3604</a>	<a href="#">PROtec-RZ-24-230</a>
<a href="#">ST4 3605</a>	<a href="#">PROtec-RZ-24-230-SB</a>
<a href="#">ST4 3608</a>	<a href="#">PROtec-RZ-24-230-SB-NA</a>