



Technical Data

Input voltage	230 V AC
Output voltage	24 V DC
Output current	10

TECHNICAL DATA

Matchcode Article name Part number Input voltage Output voltage Output current LED signs IP code Weight Housing

Housing type Colour Housing width Housing height Housing depth Environment temperature range M-VENT-10-AP (2 FMU) Ventilation control unit M-VENT-10-AP ST4 4041 230 V AC 24 V DC 10 white: WTS; yellow: failure; green: OK IP20 4.5 Sheet steel housing 301 x 323 x 85 mm (WxHxD), surface-mounting Steel case RAL 9010 white 301 323 85 -5°C - +60°C

ACCESSORIES

Part no.	Matchcode
<u>ST4 10120</u>	Pb-battery-7Ah
<u>ST4 10121</u>	<u>pb-battery-12ah</u>
<u>ST4 10122</u>	<u>pb-battery-17ah</u>
<u>ST4 10123</u>	pb-battery-24ah
<u>ST4 10124</u>	<u>Pb battery 38 Ah</u>
<u>ST4 3321</u>	Flange plate 445-130 plastic
<u>ST4 3322</u>	Flange plate 345-130 plastic
<u>ST4 3323</u>	Flange plate 545-130 plastic
<u>ST4 3344</u>	<u>HR-820-MS</u>
<u>ST4 3361</u>	Charge electronics, type LB-120
<u>ST4 3362</u>	Charge electronics, type LB-140
<u>ST4 3363</u>	Charge electronics, type LB-160



<u>ST4 3369</u>	Charge electronics, type LB-120-10
<u>ST4 3380</u>	<u>ZI-100</u>
<u>ST4 3381</u>	<u>SI-100</u>
<u>ST4 3382</u>	<u>MI-100</u>
<u>ST4 3383</u>	<u>MR-120</u>
<u>ST4 3385</u>	<u>MI-100-MB</u>
<u>ST4 3386</u>	<u>SI-100-MASTER</u>
<u>ST4 3389</u>	<u>BI-100-KNX</u>