



## **Technical Data**

SIMON LINK	
Input voltage	230 V AC
Output voltage	24 V DC
Output current	5

## **TECHNICAL DATA**

Matchcode Article name Part number Input voltage Output voltage Output current LED signs IP code Weight Housing

Housing type Colour Housing width Housing height Housing depth Environment temperature range M-VENT-5-S Ventilation control unit M-VENT-5-S ST4 4043 230 V AC 24 V DC 5 white: WTS; yellow: failure; green: OK IP66 11.5 Sheet steel housing 400 x 600 x 200 mm (WxHxD), integrated mounting Steel case RAL 7035 400 600 200 -5°C - +60°C

## ACCESSORIES

Part no.	Matchcode
<u>ST4 10120</u>	Pb-battery-7Ah
<u>ST4 10121</u>	<u>pb-battery-12ah</u>
<u>ST4 10122</u>	<u>pb-battery-17ah</u>
<u>ST4 10123</u>	pb-battery-24ah
<u>ST4 10124</u>	Pb battery 38 Ah
<u>ST4 3321</u>	Flange plate 445-130 plastic
<u>ST4 3322</u>	Flange plate 345-130 plastic
<u>ST4 3323</u>	Flange plate 545-130 plastic
<u>ST4 3344</u>	<u>HR-820-MS</u>
<u>ST4 3361</u>	Charge electronics, type LB-120
<u>ST4 3362</u>	Charge electronics, type LB-140
<u>ST4 3363</u>	Charge electronics, type LB-160



<u>ST4 3369</u>	Charge electronics, type LB-120-10
<u>ST4 3380</u>	<u>ZI-100</u>
<u>ST4 3381</u>	<u>SI-100</u>
<u>ST4 3382</u>	<u>MI-100</u>
<u>ST4 3383</u>	<u>MR-120</u>
<u>ST4 3385</u>	<u>MI-100-MB</u>
<u>ST4 3386</u>	<u>SI-100-MASTER</u>
<u>ST4 3389</u>	<u>BI-100-KNX</u>