



Technical Data



| | |
|----------------|----------|
| Input voltage | 230 V AC |
| Output voltage | 24 V DC |
| Output current | 10 |

TECHNICAL DATA

| | |
|-------------------------------|---|
| Matchcode | M-VENT-10-S |
| Article name | Ventilation control unit M-VENT-10-S |
| Part number | St4 4044 |
| Input voltage | 230 V AC |
| Output voltage | 24 V DC |
| Output current | 10 |
| LED signs | white: WTS; yellow: failure; green: OK |
| IP code | IP66 |
| Weight | 12 |
| Housing | Sheet steel housing 400 x 600 x 200 mm (WxHxD), integrated mounting |
| Housing type | Steel case |
| Colour | RAL 7035 |
| Housing width | 400 |
| Housing height | 600 |
| Housing depth | 200 |
| Environment temperature range | -5°C - +60°C |

ACCESSORIES

| Part no. | Matchcode |
|---------------------------|---|
| ST4 10120 | Pb-battery-7Ah |
| ST4 10121 | pb-battery-12ah |
| ST4 10122 | pb-battery-17ah |
| ST4 10123 | pb-battery-24ah |
| ST4 10124 | Pb battery 38 Ah |
| ST4 3321 | Flange plate 445-130 plastic |
| ST4 3322 | Flange plate 345-130 plastic |
| ST4 3323 | Flange plate 545-130 plastic |
| ST4 3344 | HR-820-MS |
| ST4 3361 | Charge electronics, type LB-120 |
| ST4 3362 | Charge electronics, type LB-140 |
| ST4 3363 | Charge electronics, type LB-160 |

| | |
|--------------------------|--|
| ST4 3369 | Charge electronics, type LB-120-10 |
| ST4 3380 | ZI-100 |
| ST4 3381 | SI-100 |
| ST4 3382 | MI-100 |
| ST4 3383 | MR-120 |
| ST4 3385 | MI-100-MB |
| ST4 3386 | SI-100-MASTER |
| ST4 3389 | BI-100-KNX |