

Ventilation control unit M-VENT-40-S



Technical Data



Input voltage 230 V AC
Output voltage 24 V DC
Output current 40

TECHNICAL DATA

Matchcode M-VENT-40-S
Article name Ventilation control unit M-VENT-40-S
Part number ST4 4046

Input voltage 230 V AC
Output voltage 24 V DC
Output current 40

LED signs white: WTS; yellow: failure; green: OK

IP code IP66 Weight 13.5

Housing Sheet steel housing 400 x 600 x 200 mm

(WxHxD), integrated mounting

Housing typeSteel caseColourRAL 7035Housing width400Housing height600Housing depth200

Environment temperature range -5°C - +60°C

ACCESSORIES

| Part no. | Matchcode |
|-----------|---------------------------------|
| ST4 10120 | Pb-battery-7Ah |
| ST4 10121 | pb-battery-12ah |
| ST4 10122 | pb-battery-17ah |
| ST4 10123 | pb-battery-24ah |
| ST4 10124 | Pb battery 38 Ah |
| ST4 3321 | Flange plate 445-130 plastic |
| ST4 3322 | Flange plate 345-130 plastic |
| ST4 3323 | Flange plate 545-130 plastic |
| ST4 3344 | HR-820-MS |
| ST4 3361 | Charge electronics, type LB-120 |
| ST4 3362 | Charge electronics, type LB-140 |
| ST4 3363 | Charge electronics, type LB-160 |



Ventilation control unit M-VENT-40-S

| ST4 3369 | Charge electronics, type LB-120-10 |
|----------|------------------------------------|
| ST4 3380 | <u>ZI-100</u> |
| ST4 3381 | <u>SI-100</u> |
| ST4 3382 | <u>MI-100</u> |
| ST4 3383 | MR-120 |
| ST4 3385 | MI-100-MB |
| ST4 3386 | SI-100-MASTER |
| ST4 3389 | <u>BI-100-KNX</u> |
| | |