



## Technical Data



Input voltage	230 V AC
Output voltage	24 V DC
Output current	48

## TECHNICAL DATA

Matchcode	M-VENT-48
Article name	Ventilation control unit M-VENT-48
Part number	ST4 4046
Input voltage	230 V AC
Output voltage	24 V DC
Output current	48
LED signs	white: WTS; yellow: failure; green: OK
IP code	IP66
Weight	13.5
Housing	Sheet steel housing 400 x 600 x 200 mm (WxHxD), integrated mounting
Housing type	Steel case
Colour	RAL 7035
Housing width	400
Housing height	600
Housing depth	200
Environment temperature range	-5°C - +60°C

## ACCESSORIES

Part no.	Matchcode
<a href="#">ST4 10120</a>	<a href="#">Pb-battery-7Ah</a>
<a href="#">ST4 10121</a>	<a href="#">pb-battery-12ah</a>
<a href="#">ST4 10122</a>	<a href="#">pb-battery-17ah</a>
<a href="#">ST4 10123</a>	<a href="#">pb-battery-24ah</a>
<a href="#">ST4 10124</a>	<a href="#">Pb battery 38 Ah</a>
<a href="#">ST4 3321</a>	<a href="#">Flange plate 445-130 plastic</a>
<a href="#">ST4 3322</a>	<a href="#">Flange plate 345-130 plastic</a>
<a href="#">ST4 3323</a>	<a href="#">Flange plate 545-130 plastic</a>
<a href="#">ST4 3344</a>	<a href="#">HR-820-MS</a>
<a href="#">ST4 3380</a>	<a href="#">ZI-100</a>
<a href="#">ST4 3381</a>	<a href="#">SI-100</a>
<a href="#">ST4 3382</a>	<a href="#">MI-100</a>

[ST4 3383](#)

[MR-120](#)

[ST4 3385](#)

[MI-100-MB](#)

[ST4 3386](#)

[SI-100-MASTER](#)

[ST4 3389](#)

[BI-100-KNX](#)