



## Technical Data



Input voltage	230 V AC
Output voltage	24 V DC
Output current	12
SHE Groups	1
Ventilation groups	1

## TECHNICAL DATA

Matchcode	M-SHEV-12-AP
Article name	Modular control panel M-SHEV-12-AP
Part number	ST4 3460
Input voltage	230 V AC
Output voltage	24 V DC
Output current	12
Classification	CE certified EN 12101-10, tested ISO 21927-9
LED signs	LED display operating status network: Permanent display green - mains available LED display operating status lead acid battery ("O.K."): Continuous green - battery is present and charging (charge is being maintained)
IP code	IP20
SHE Groups	1
Ventilation groups	1
Weight	14.3
Housing	Sheet steel case
Housing type	Steel case
Colour	RAL 9010
Housing width	400
Housing height	516
Housing depth	155
Appliance class	I
Environment temperature range	-5°C - +40°C

## ACCESSORIES

Part no.	Matchcode
<a href="#">ST4 10120</a>	<a href="#">Pb-battery-7Ah</a>
<a href="#">ST4 10121</a>	<a href="#">pb-battery-12ah</a>
<a href="#">ST4 10122</a>	<a href="#">pb-battery-17ah</a>
<a href="#">ST4 10123</a>	<a href="#">pb-battery-24ah</a>
<a href="#">ST4 10124</a>	<a href="#">Pb battery 38 Ah</a>
<a href="#">ST4 3321</a>	<a href="#">Flange plate 445-130 plastic</a>
<a href="#">ST4 3322</a>	<a href="#">Flange plate 345-130 plastic</a>

---

<a href="#"><u>ST4 3323</u></a>	<a href="#"><u>Flange plate 545-130 plastic</u></a>
<a href="#"><u>ST4 3344</u></a>	<a href="#"><u>HR-820-MS</u></a>
<a href="#"><u>ST4 33516</u></a>	<a href="#"><u>AP-MOUNT</u></a>
<a href="#"><u>ST4 3380</u></a>	<a href="#"><u>ZI-100</u></a>
<a href="#"><u>ST4 3381</u></a>	<a href="#"><u>SI-100</u></a>
<a href="#"><u>ST4 3382</u></a>	<a href="#"><u>MI-100</u></a>
<a href="#"><u>ST4 3383</u></a>	<a href="#"><u>MR-120</u></a>
<a href="#"><u>ST4 3385</u></a>	<a href="#"><u>MI-100-MB</u></a>
<a href="#"><u>ST4 3386</u></a>	<a href="#"><u>SI-100-MASTER</u></a>
<a href="#"><u>ST4 3389</u></a>	<a href="#"><u>BI-100-KNX</u></a>