



Technical Data



TECHNICAL DATA

| | |
|---------------------|--|
| Matchcode | FSV-MARC-SFS-EI120 |
| Article name | Fire Curtain Fire PROtec EI 120 MARC |
| Part number | FSV 54106 |
| Classification | EI 90 / EI 120 C2 according EN 13051-2 CE marking according EN 16034 |
| Fabric | Multiple layer silicone coated fabric with insulating material |
| Unwind | Through gravity (gravity fail safe) |
| Rewind | Through integrated tubular motor 230 V AC or external 400 V AC motor |
| System installation | Reveal and wall mounting |
| System size | 18,000 x 10,000 mm |
| Housing | Head-box EI120: 325 x 350 bis 775 x 800 mm; Side guides: 120 x 80 mm; from curtain dimensions (W x H) 6000 x 2000mm: 140 x 80 mm; Galvanized steel |
| Bottom Bar | Round steel bar in bottom fabric pocket |
| Housing type | Steel case |

ACCESSORIES

| Part no. | Matchcode |
|---------------------------|---|
| A3 2054 | RM 2860 FSV |
| A3 2167 | HE-088-YELLOW-ALU |
| A3 2168 | HE-088-ORANGE-ALU |
| RSV 60016 | Fire PROtec² EI MARC - repair tape |
| ST4 3604 | PROtec-RZ-24-230 |
| ST4 3605 | PROtec-RZ-24-230-SB |
| ST4 3606 | PROtec-RZ-24-400 |
| ST4 3607 | PROtec-RZ-24-400-SB |