



Technical Data



TECHNICAL DATA

Matchcode	FSV2-182-XL-SFS-EW30
Article name	Fire curtain Fire PROtec ² FSV2-182-XL-SFS-EW30
Part number	FSV2 2012
Classification	E 30 EW 30 with CE according to EN 16034, VKF approval for Switzerland #31653
Fabric	Fire retardant polyurethane coated e-glass fabric in grey 690 g/m ² (A2 EN 13501-1)
Unwind	descending by gravity (fail safe)
Rewind	planet drive, 24 V DC, 3 A with electric load breaking; roll shaft-integrated.
System installation	Only wall mounting on the side facing the fire
System size	max. 4400 x 3000 mm (WxH)
Housing	Head box (W x H): Galvanized sheet steel 1.5 mm (150 x 182 mm, two-piece); Side guides (W x H): Galvanized sheet steel 2 mm (58 x 95 mm)
Bottom Bar	Galvanised steel 2 mm with integrated springs and round steel in fabric bag for gravity fail-safe
Housing type	Steel case
Housing width	150
Housing height	182

ACCESSORIES

Part no.	Matchcode
A3 2064	RM 3000 FSV
A3 2167	HE-088-YELLOW-ALU
A3 2168	HE-088-ORANGE-ALU
A3 2178	HE 087 Yellow FSV
A3 4574	CT/NA/Rot
ST4 3601	PROtec-RZ-24
ST4 3602	PROtec-RZ-24-SB
ST4 3603	PROtec-RZ-24-SB-NA