



**Technical Data**



**TECHNICAL DATA**

Matchcode	FSV2-212-SFS-EW30
Article name	Fire curtain Fire PROtec <sup>2</sup> FSV2-212-SFS-EW30
Part number	FSV2 2013
Classification	E 30 EW 30 with CE according to EN 16034, VKF approval for Switzerland #31653
Fabric	Fire retardant polyurethane coated e-glass fabric in grey 690 g/m <sup>2</sup> (A2   EN 13501-1)
Unwind	descending by gravity (fail safe)
Rewind	planet drive, 24 V DC, 3 A with electric load breaking; roll shaft-integrated.
System installation	Only wall mounting on the side facing the fire
System size	max. 2800 x 4470 mm (WxH)
Housing	Head box (W x H): Galvanized sheet steel 1.5 mm (180 x 212 mm, one-piece); Side guides (W x H): Galvanized sheet steel 2mm (58 x 95 mm)
Bottom Bar	Galvanised steel 2 mm with integrated springs and round steel in fabric bag for gravity fail-safe
Housing type	Steel case
Housing width	180
Housing height	212

**ACCESSORIES**

Part no.	Matchcode
<a href="#">A3 2064</a>	<a href="#">RM 3000 FSV</a>
<a href="#">A3 2167</a>	<a href="#">HE-088-YELLOW-ALU</a>
<a href="#">A3 2168</a>	<a href="#">HE-088-ORANGE-ALU</a>
<a href="#">A3 2178</a>	<a href="#">HE 087 Yellow FSV</a>
<a href="#">A3 4574</a>	<a href="#">CT/NA/Rot</a>
<a href="#">ST4 3601</a>	<a href="#">PROtec-RZ-24</a>
<a href="#">ST4 3602</a>	<a href="#">PROtec-RZ-24-SB</a>
<a href="#">ST4 3603</a>	<a href="#">PROtec-RZ-24-SB-NA</a>