



Technical Data



TECHNICAL DATA

Matchcode	M-SHEV-24-RSV
Article name	Modular control panel M-SHEV-24-RSV
Part number	ST4 3422
Input voltage	230 V AC
Output voltage	24 V DC
Output current	24
LED signs	LEDs on the loading card: 1. green LED "AKKU" = OK (Akku exists and is loading) 2. green LED "NETZ" = mains operation further LEDs on the modules
IP code	IP54
Mounting way	aufgesetzt
Housing	Steel case housing 500x500x200 mm
Housing type	Steel case
Colour	RAL 7035 light grey
Housing length	500
Housing width	500
Housing height	250
Appliance class	I
Environment temperature range	-5 °C bis 40 °C

ACCESSORIES

Part no.	Matchcode
ST4 10120	Pb-battery-7Ah
ST4 10121	pb-battery-12ah
ST4 10122	pb-battery-17ah
ST4 10123	pb-battery-24ah
ST4 10124	Pb battery 38 Ah
ST4 3321	Flange plate 445-130 plastic
ST4 3322	Flange plate 345-130 plastic
ST4 3323	Flange plate 545-130 plastic
ST4 3361	Charge electronics, type LB-120
ST4 3362	Charge electronics, type LB-140

ST4 3363	Charge electronics, type LB-160
ST4 3369	Charge electronics, type LB-120-10
ST4 3380	ZI-100
ST4 3381	SI-100
ST4 3382	MI-100
ST4 3383	MR-120
ST4 3386	SI-100-MASTER