



## Technical Data



Input voltage	24 V DC
Nominal current	1.6
Opening angle	122
IP code	IP54
Switch on duration	30

## MOUNTING POSITIONS



## TECHNICAL DATA

Matchcode	PA-KL <sup>2</sup> -T-50/122deg
Article name	Folding arm <sup>2</sup> door opener PA-KL <sup>2</sup> -T-50
Part number	M2 2021
Input voltage	24 V DC
Nominal current	1.6
Input voltage range	- 15 % / + 15 %
Ripple	500
Opening angle	122
Push force	500
Pull force	50
Classification	EN 12101-2, EN 60335-1, EN 60335-2-103
Cut-Off	Integrated overload cut-off with microprocessor
Running speed	2
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	4.22
Housing	Aluminium housing E6 / EV1 anodized
Housing type	Aluminium
Colour	RAL & DB colors
Housing length	474
Housing width	58
Housing height	118
Appliance class	III

Connection cable	SICO PLUG connection. Excluding connection cable / set.
Nominal working temperature	20
Environment temperature range	0 °C - 75 °C
Brackets included	nein

### ACCESSORIES

Part no.	Matchcode
<a href="#">K2 1620</a>	<a href="#">K-KL<sup>2</sup>-T-MW</a>
<a href="#">K2 1621</a>	<a href="#">K-KL<sup>2</sup>-T-MP</a>
<a href="#">K2 2001</a>	<a href="#">SICO-PLUG</a>
<a href="#">K2 2002</a>	<a href="#">SICO-PLUG-SP</a>
<a href="#">K2 2003</a>	<a href="#">PA-ANL-SIHF-6x0,5mm<sup>2</sup></a>
<a href="#">K2 2004</a>	<a href="#">PA-ANL-3m</a>
<a href="#">K2 2005</a>	<a href="#">PA-ANL-5m</a>
<a href="#">K2 2006</a>	<a href="#">PA-ANL-+lfm</a>
<a href="#">K2 2007</a>	<a href="#">PA-SICO-SET-3m</a>
<a href="#">K2 2008</a>	<a href="#">PA-SICO-SET-5m</a>
<a href="#">K2 2009</a>	<a href="#">PA-SICO-SET-+lfm</a>
<a href="#">SD1 8513</a>	<a href="#">SICO-LINK-USB-110</a>
<a href="#">SD1 8514</a>	<a href="#">SICO-PLUG-INSTALL</a>
<a href="#">SD1 8522</a>	<a href="#">SICO-LINK-Adapter</a>
<a href="#">SD1 8525</a>	<a href="#">SICO-PLUCKER</a>
<a href="#">SD1 8530</a>	<a href="#">Software parameterization</a>