




## Technical Data



Input voltage	24 V DC
Nominal current	3.0
Opening angle	122
IP code	IP54
Switch on duration	30

## MOUNTING POSITIONS



## TECHNICAL DATA

Matchcode	PA-KL <sup>2</sup> -T-80/122deg
Article name	Folding arm <sup>2</sup> door opener PA-KL <sup>2</sup> -T-80
Part number	M2 2022
Input voltage	24 V DC
Nominal current	3.0
Input voltage range	- 15 % / + 15 %
Ripple	500
Opening angle	122
Push force	800
Pull force	50
Classification	EN 12101-2, EN 60335-1, EN 60335-2-103
Cut-Off	Integrated overload cut-off with microprocessor
Running speed	2
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	6.20
Housing	Aluminium housing E6 / EV1 anodized
Housing type	Aluminium
Colour	RAL & DB colors
Housing length	574
Housing width	68
Housing height	118
Appliance class	III
Connection cable	SICO PLUG connection. Excluding connection cable / set.
Nominal working temperature	20
Environment temperature range	0 °C - 75 °C
Brackets included	nein

**ACCESSORIES**

Part no.	Matchcode	
<a href="#">K2 1660</a>	<a href="#">K-KL<sup>2</sup>-T-80-MW</a>	
<a href="#">K2 2001</a>	<a href="#">SICO-PLUG</a>	
<a href="#">K2 2002</a>	<a href="#">SICO-PLUG-SP</a>	
<a href="#">K2 2003</a>	<a href="#">PA-ANL-SIHF-6x0,5mm<sup>2</sup></a>	
<a href="#">K2 2004</a>	<a href="#">PA-ANL-3m</a>	
<a href="#">K2 2005</a>	<a href="#">PA-ANL-5m</a>	
<a href="#">K2 2006</a>	<a href="#">PA-ANL-+lfm</a>	
<a href="#">K2 2007</a>	<a href="#">PA-SICO-SET-3m</a>	
<a href="#">K2 2008</a>	<a href="#">PA-SICO-SET-5m</a>	
<a href="#">K2 2009</a>	<a href="#">PA-SICO-SET-+lfm</a>	
<a href="#">SD1 8513</a>	<a href="#">SICO-LINK-USB-110</a>	
<a href="#">SD1 8514</a>	<a href="#">SICO-PLUG-INSTALL</a>	
<a href="#">SD1 8530</a>	<a href="#">Software parameterization</a>	