



## Technical Data



|                    |         |
|--------------------|---------|
| Input voltage      | 24 V DC |
| Nominal current    | 1.3     |
| Opening angle      | 122     |
| IP code            | IP54    |
| Switch on duration | 30      |

## MOUNTING POSITIONS



## TECHNICAL DATA

|                               |   |
|-------------------------------|---|
| Matchcode                     | PA-KL <sup>2</sup> -T-K-50/122deg                               |
| Article name                  | Folding Arm <sup>2</sup> door opener PA-KL <sup>2</sup> -T-K-50 |
| Part number                   | M2 2023   |
| Input voltage                 | 24 V DC   |
| Nominal current               | 1.3   |
| Input voltage range           | - 15 % / + 15 %   |
| Ripple                        | 500   |
| Networked standby             | 0.9 W (1 min)   |
| Opening angle                 | 122   |
| Push force                    | 500   |
| Pull force                    | 50  |
| Classification                | EN 12101-2, EN 60335-1, EN 60335-2-103                          |
| Cut-Off                       | Integrated overload cut-off with microprocessor                 |
| Running speed                 | 2   |
| IP code                       | IP54  |
| Switch on duration            | 30  |
| Weight                        | 3.7   |
| Housing                       | Aluminium housing E6 / EV1 anodized                             |
| Housing type                  | Aluminium   |
| Colour                        | RAL & DB colors   |
| Housing length                | 382   |
| Housing width                 | 58  |
| Housing height                | 118   |
| Appliance class               | III   |
| Connection cable              | SICO PLUG connection. Excluding connection cable / set.         |
| Nominal working temperature   | 20  |
| Environment temperature range | 0 °C - 75 °C  |
| Brackets included             | nein  |

## ACCESSORIES

| Part no.                 | Matchcode                                       |  |
|--------------------------|---|--|
| <a href="#">K2 1620</a>  | <a href="#">K-KL<sup>2</sup>-T-MW</a>           |  |
| <a href="#">K2 1621</a>  | <a href="#">K-KL<sup>2</sup>-T-MP</a>           |  |
| <a href="#">K2 2001</a>  | <a href="#">SICO-PLUG</a>                       |  |
| <a href="#">K2 2002</a>  | <a href="#">SICO-PLUG-SP</a>                    |  |
| <a href="#">K2 2003</a>  | <a href="#">PA-ANL-SIHF-6x0.5mm<sup>2</sup></a> |  |
| <a href="#">K2 2004</a>  | <a href="#">PA-ANL-3m</a>                       |  |
| <a href="#">K2 2005</a>  | <a href="#">PA-ANL-5m</a>                       |  |
| <a href="#">K2 2006</a>  | <a href="#">PA-ANL-+lfm</a>                     |  |
| <a href="#">K2 2007</a>  | <a href="#">PA-SICO-SET-3m</a>                  |  |
| <a href="#">K2 2008</a>  | <a href="#">PA-SICO-SET-5m</a>                  |  |
| <a href="#">K2 2009</a>  | <a href="#">PA-SICO-SET-+lfm</a>                |  |
| <a href="#">SD1 8513</a> | <a href="#">SICO-LINK-USB-110</a>               |  |
| <a href="#">SD1 8514</a> | <a href="#">SICO-PLUG-INSTALL</a>               |  |
| <a href="#">SD1 8522</a> | <a href="#">SICO-LINK-Adapter</a>               |  |
| <a href="#">SD1 8525</a> | <a href="#">SICO-PLUCKER</a>                    |  |
| <a href="#">SD1 8530</a> | <a href="#">Software parameterization</a>       |  |