



## Technical Data



### ARTICLE INFO

The glass louvre system TG-24-RWA offers architects or facade planners an extensive scope of design. Therefore it is frequently applied in combination with smoke exhausting concepts and due to its **large ventilation cross sections** it is not only an ideal solution for smoke and heat exhaust vent openings but also for inlet air systems.

The glass louvre system, type TG-24-RWA is a smoke and heat ventilation device **tested according to EN 12101-2**. With regard to temperature resistance, permanent load, aerodynamic efficiency and further test criteria such as wind load resistance, the glass louvre system offers a maximum of safety. Of course, in addition to the SHEV function, the glass louvre system can also be used for ventilation purposes.

An electromechanical slit actuator type EA-L/S-1000/48 manufactured by SIMON PROtec and specially adapted to the lamella system is used as motor.

### Technical data

Glass louvre window type TG-24-RWA for smoke and heat exhaust ventilation (SHEV)

Type: Thermal broken aluminium profiles

Drainage: Over 7° outside tilt profile

Surface: Anodized (or optional RAL coating)

Connecting parts and joints: High-grade steel, concealed bars

Frame: depth 66,4 mm

Static profile: With two isolating bars

Glazing: ISO Glass 24 mm (2 x Float 4 mm, 16 mm LZR)

Louvres: Centre pivot

Insulation: value 2,1 W/m<sup>2</sup>K

Heat protection: K - value 1.1

Heat resistance: B 300, up to 300° C (SHEV operation)\*

Environmental temperature: T(-15), up to -15° C (SHEV operation)\*

Wind load: WL A, 4.500 Pa\*

Reliability: RE 1000, 10.000 (ventilation) + 1.000 (SHEV) load alternations\*

\* Classification and test criteria according to DIN EN 12101-2

**Note:** The louvre window TG-24-RWA is only qualified for vertical installation.

### TECHNICAL DATA

Matchcode

Louvre window TG-24-SHEV

Article name  
Part number

Louvre window TG-24-SHEV  
RWG 50110

## ACCESSORIES

Part no.	Matchcode	
<a href="#">M2 1740</a>	<a href="#">EA-L/S-1000/48-02</a>	