

# Linear actuator PA-L-180/500-S



## **Technical Data**







4



24 V DC Input voltage


Nominal current

Running speed 12.5

IP code IP54

Switch on duration 30

#### **MOUNTING POSITIONS**



## **TECHNICAL DATA**

Matchcode PA-L-180/500-S Linear actuator PA-L-180/500-S Article name Part number M2 2442 S Input voltage 24 V DC

Nominal current

- 15 % / + 15 % Input voltage range Networked standby 0.9 W (1 min)

Stroke 500 Push force 1800 Pull force 1800 Nominal locking force 2200

Cut-Off external electronic overload cut-off

Running speed 12.5 IP54 IP code Switch on duration 30

Mounting way aufgesetzt

Weight 5.7

Aluminium profile tube E6/EV1 anodized, with Housing integrated mount for flexible bracket system,

length: 416 mm + stroke

Aluminium Housing type Colour **RAL 9006** Housing length 917 58

Diameter



# Linear actuator PA-L-180/500-S

Appliance class Connection cable

Nominal working temperature Environment temperature range Brackets included Customs tariff no II SICO PLUG connection. Excluding connection cable / set. 20 -5 °C - 75 °C ja 84798997

Part no.	Matchcode
K2 1501 B	<u>OK-1500</u>
<u>K2 1585</u>	<u>K-L-UK-180</u>
<u>K2 2004</u>	PA-ANL-3m
<u>K2 2005</u>	PA-ANL-5m
<u>K2 2006</u>	PA-ANL-+lfm
<u>K2 2007</u>	PA-SICO-SET-3m
K2 2008	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER