



## Technical Data



Input voltage	24 V DC
Nominal current	1.0
Running speed	7.7
IP code	IP54
Switch on duration	30

## MOUNTING POSITIONS



## TECHNICAL DATA

Matchcode	PA-LS-50/300
Article name	Slit actuator PA-LS-50/300
Part number	M2 2462
Input voltage	24 V DC
Nominal current	1.0
Networked standby	0.9 W (1 min)
Stroke	281
Push force	500
Pull force	500
Nominal locking force	1000
Cut-Off	integrated electronic overload cut-off
Running speed	7.7
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	2.1
Housing	Aluminium profile tube, anodised E6/EV1 with integrated holder for flexible bracket system
Housing type	Aluminium
Colour	On request
Housing length	635
Housing height	42
Diameter	36
Appliance class	III
Connection cable	SICO PLUG connection. Excluding connection cable / set.
Nominal working temperature	20
Environment temperature range	-5 °C - 75 °C
Brackets included	ja
Customs tariff no	84798997

## ACCESSORIES

Part no.	Matchcode	
<a href="#">K2 1505 A</a>	<a href="#">UKU-740</a>	
<a href="#">K2 1539</a>	<a href="#">HK-L</a>	
<a href="#">K2 1563</a>	<a href="#">K-L-UK-J</a>	
<a href="#">K2 2004</a>	<a href="#">PA-ANL-3m</a>	
<a href="#">K2 2005</a>	<a href="#">PA-ANL-5m</a>	
<a href="#">K2 2006</a>	<a href="#">PA-ANL-+lfm</a>	
<a href="#">K2 2007</a>	<a href="#">PA-SICO-SET-3m</a>	
<a href="#">K2 2008</a>	<a href="#">PA-SICO-SET-5m</a>	
<a href="#">K2 2009</a>	<a href="#">PA-SICO-SET-+lfm</a>	
<a href="#">SD1 8522</a>	<a href="#">SICO-LINK-Adapter</a>	
<a href="#">SD1 8525</a>	<a href="#">SICO-PLUCKER</a>	