

Linear actuator PA-L-50/750

Technical Data











Input voltage 24 V DC

Nominal current 1.0
Running speed 7.7
IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-50/750
Article name Linear actuator PA-L-50/750

Part number M2 2404
Input voltage 24 V DC

Nominal current 1.0 Input voltage range -15 % / + 15 %

Networked standby

Stroke

Push force

750

500

Push force500Pull force500Nominal locking force1000

Cut-Off integrated electronic overload cut-off

Running speed 7.7
IP code IP54
Switch on duration 30
Mounting way aufg

Mounting way aufgesetzt Weight 2.85

Housing end-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

Housing type Aluminium
Colour On request

Housing length 1137
Housing height 42
Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-50/750

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

| ACCESSORIES | |
|------------------|--------------------------------|
| Part no. | Matchcode |
| K2 1501 | <u>OK</u> |
| K2 1502 | DAS |
| <u>K2 1505 A</u> | <u>UKU-740</u> |
| <u>K2 1506</u> | <u>AW 100-6</u> |
| K2 1506 A | AW 100-6-A |
| K2 1507 A | <u>AW 150-6</u> |
| K2 1507 B | <u>AW 150-6-A</u> |
| K2 1519 A | AW 250-6 |
| <u>K2 1539</u> | <u>HK-L</u> |
| K2 1562 | <u>UK-L</u> |
| <u>K2 1563</u> | <u>K-L-UK-J</u> |
| <u>K2 1576</u> | K-L-RAICO105D-RE-9006 (rechts) |
| <u>K2 1577</u> | K-L-RAICO105D-LI-9006 (links) |
| K2 1601 | K-L-A-LI-AW57RO |
| K2 1603 | K-L-A-RE-AW57RO |
| <u>K2 2004</u> | PA-ANL-3m |
| <u>K2 2005</u> | PA-ANL-5m |
| <u>K2 2006</u> | PA-ANL-+Ifm |
| K2 2007 | PA-SICO-SET-3m |
| K2 2008 | PA-SICO-SET-5m |
| K2 2009 | PA-SICO-SET-+Ifm |
| SD1 8522 | SICO-LINK-Adapter |
| SD1 8525 | SICO-PLUCKER |