

Linear actuator PA-L-50/1000

Technical Data











Input voltage 24 V DC

Nominal current 1.0
Running speed 7.7
IP code IP54

Switch on duration 30

MOUNTING POSITIONS















Housing type











TECHNICAL DATA

Matchcode PA-L-50/1000
Article name Linear actuator PA-L-50/1000

Part number M2 2405
Input voltage 24 V DC
Nominal current 1.0

Input voltage range -15% / +15%Networked standby 0.9 W (1 min)Stroke 1000

Push force 500
Pull force 500
Nominal locking force 1000

Cut-Off integrated electronic overload cut-off

Running speed 7.7
IP code IP54
Switch on duration 30

Mounting way aufgesetzt Weight 3.55

Housing end-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

bracket system Aluminium

ColourOn requestHousing length1387Housing height42Diameter36Appliance classIII

Connection cable SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-50/1000

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES		
Part no.	Matchcode	
K2 1501	OK	
<u>K2 1502</u>	<u>DAS</u>	
K2 1505 A	<u>UKU-740</u>	
K2 1506	AW 100-6	
K2 1506 A	AW 100-6-A	
K2 1507 A	<u>AW 150-6</u>	
K2 1507 B	AW 150-6-A	
K2 1519 A	<u>AW 250-6</u>	
K2 1539	HK-L	
K2 1562	<u>UK-L</u>	
<u>K2 1563</u>	K-L-UK-J	
<u>K2 2004</u>	PA-ANL-3m	
<u>K2 2005</u>	PA-ANL-5m	
K2 2006	PA-ANL-+Ifm	
<u>K2 2007</u>	PA-SICO-SET-3m	
<u>K2 2008</u>	PA-SICO-SET-5m	
<u>K2 2009</u>	PA-SICO-SET-+Ifm	
SD1 8522	SICO-LINK-Adapter	
SD1 8525	SICO-PLUCKER	