

Linear actuator PA-L-50/200

Technical Data











Input voltage 24 V DC

Nominal current 1.0 Running speed 7.7

IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-50/200

Article name Linear actuator PA-L-50/200 Part number M2 2401

Input voltage M2 24 V DC
Nominal current 1.0

 $\begin{array}{ccc} \text{Input voltage range} & & \text{- 15 \% /+ 15 \%} \\ \text{Networked standby} & & \text{0.9 W (1 min)} \end{array}$

Stroke200Push force500Pull force500Nominal locking force1000

Cut-Off integrated electronic overload cut-off

Running speed 7.7
IP code IP54
Switch on duration 30

Mounting way aufgesetzt Weight 1.45

Housing end-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

Housing type Aluminium
Colour On request

Housing length 587
Housing height 42
Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-50/200

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES	
Part no.	Matchcode
K2 1501	OK
K2 1502	DAS
<u>K2 1505 A</u>	<u>UKU-740</u>
K2 1506	AW 100-6
K2 1506 A	AW 100-6-A
K2 1507 A	AW 150-6
<u>K2 1507 B</u>	AW 150-6-A
K2 1519 A	AW 250-6
K2 1539	<u>HK-L</u>
<u>K2 1562</u>	<u>UK-L</u>
<u>K2 1563</u>	K-L-UK-J
K2 2004	PA-ANL-3m
K2 2005	PA-ANL-5m
K2 2006	PA-ANL-+Ifm
K2 2007	PA-SICO-SET-3m
K2 2008	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER