

Linear actuator PA-L-75/300

Technical Data







30





Input voltage 24 V DC

Nominal current 1.1
Running speed 7.6
IP code IP54

MOUNTING POSITIONS









Switch on duration

















TECHNICAL DATA

Matchcode
Article name
Part number
Input voltage
Nominal current
Input voltage range
Networked standby

Stroke Push force Pull force

Nominal locking force

Cut-Off

Running speed

IP code

Switch on duration Mounting way

Weight Housing

Housing type

Colour Housing length Housing height Diameter Appliance class

Connection cable

PA-L-75/300

Linear actuator PA-L-75/300

M2 2412 24 V DC 1.1

- 15 % / + 15 % 0.9 W (1 min)

integrated electronic overload cut-off

7.6 IP54 30

aufgesetzt

1.7

end-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

bracket system
Aluminium

On request 687 42 36

SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-75/300

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES	
Part no.	Matchcode
K2 1501	<u>OK</u>
<u>K2 1502</u>	<u>DAS</u>
<u>K2 1505 A</u>	<u>UKU-740</u>
<u>K2 1506</u>	<u>AW 100-6</u>
K2 1506 A	<u>AW 100-6-A</u>
K2 1507 A	AW 150-6
K2 1507 B	AW 150-6-A
K2 1519 A	AW 250-6
K2 1539	HK-L
K2 1562	<u>UK-L</u>
K2 1563	<u>K-L-UK-J</u>
<u>K2 1576</u>	K-L-RAICO105D-RE-9006 (rechts)
<u>K2 1577</u>	K-L-RAICO105D-LI-9006 (links)
K2 1601	K-L-A-LI-AW57RO
K2 1603	K-L-A-RE-AW57RO
K2 2004	PA-ANL-3m
K2 2005	PA-ANL-5m
K2 2006	PA-ANL-+Ifm
K2 2007	PA-SICO-SET-3m
<u>K2 2008</u>	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER