

## Linear actuator PA-L-50/750\_copy

### **Technical Data**







30





Input voltage 24 V DC

Nominal current 1.1
Running speed 7.6
IP code IP54

#### **MOUNTING POSITIONS**









Switch on duration

















#### **TECHNICAL DATA**

Matchcode PA-L-75/750
Article name Linear actuator PA-L-50/750 copy

Part number M2 2414
Input voltage 24 V DC
Nominal current 1.1

Input voltage range  $$-15\ \%\ /+15\ \%$$  Stroke 750

Push force 750
Pull force 750
Nominal locking force 1000

Cut-Off integrated electronic overload cut-off

Running speed 7.6
IP code IP54
Switch on duration 30

Mounting way aufgesetzt
Weight 2.85

Housing end-to-end aluminium profile tube, anodized in

E6/EV1 with integrated retainer for flexible bracket system

Housing type Aluminium
Colour On request
Housing length 1137
Housing height 42

Housing height 42
Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.

Nominal working temperature 20



# Linear actuator PA-L-50/750\_copy

Environment temperature range Brackets included Customs tariff no -5 °C - 75 °C nein 84798997

Part no.	Matchcode
<u>K2 1501</u>	<u>OK</u>
<u>K2 1502</u>	<u>DAS</u>
<u>K2 1505 A</u>	<u>UKU-740</u>
<u>K2 1506</u>	AW 100-6
<u>K2 1506 A</u>	AW 100-6-A
<u>K2 1507 A</u>	AW 150-6
<u>K2 1507 B</u>	AW 150-6-A
<u>K2 1519 A</u>	AW 250-6
K2 1539	<u>HK-L</u>
K2 1562	<u>UK-L</u>
<u>K2 1563</u>	K-L-UK-J
<u>K2 1576</u>	K-L-RAICO105D-RE-9006 (rechts)
<u>K2 1577</u>	K-L-RAICO105D-LI-9006 (links)
<u>K2 1601</u>	K-L-A-LI-AW57RO
K2 1603	K-L-A-RE-AW57RO
K2 2004	PA-ANL-3m
K2 2005	PA-ANL-5m
<u>K2 2006</u>	PA-ANL-+Ifm
<u>K2 2007</u>	PA-SICO-SET-3m
<u>K2 2008</u>	PA-SICO-SET-5m
<u>K2 2009</u>	PA-SICO-SET-+lfm