

Linear actuator PA-L-100/500

Technical Data











Input voltage 24 V DC

Nominal current 1.0
Running speed 4.4
IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-100/500
Article name Linear actuator PA-L-100/500
Part number M2 2423

Input voltage 24 V DC
Nominal current 1.0

 $\begin{array}{ccc} \text{Input voltage range} & & -15 \ \% \ / + 15 \ \% \\ \text{Networked standby} & & 0.9 \ \text{W (1 min)} \\ \text{Stroke} & & 500 \end{array}$

Stroke500Push force1000Pull force1000Nominal locking force1000

Cut-Off integrated electronic overload cut-off

Running speed 4.4
IP code IP54
Switch on duration 30

Mounting way aufgesetzt Weight 2.2

Housing end-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

Housing type Aluminium
Colour On request

Housing length 887
Housing height 42
Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-100/500

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES	
Part no.	Matchcode
K2 1501	<u>OK</u>
K2 1502	<u>DAS</u>
<u>K2 1505 A</u>	<u>UKU-740</u>
<u>K2 1506</u>	AW 100-6
K2 1506 A	AW 100-6-A
K2 1507 A	AW 150-6
K2 1507 B	AW 150-6-A
K2 1519 A	AW 250-6
K2 1539	<u>HK-L</u>
K2 1562	<u>UK-L</u>
<u>K2 1563</u>	<u>K-L-UK-J</u>
<u>K2 1576</u>	K-L-RAICO105D-RE-9006 (rechts)
<u>K2 1577</u>	K-L-RAICO105D-LI-9006 (links)
K2 1601	K-L-A-LI-AW57RO
K2 1603	K-L-A-RE-AW57RO
K2 2004	PA-ANL-3m
K2 2005	PA-ANL-5m
<u>K2 2006</u>	PA-ANL-+Ifm
<u>K2 2007</u>	PA-SICO-SET-3m
K2 2008	PA-SICO-SET-5m
<u>K2 2009</u>	PA-SICO-SET-+lfm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER