


Technical Data



| | |
|--------------------|---------|
| Input voltage | 24 V DC |
| Nominal current | 1.1 |
| Running speed | 7.6 |
| IP code | IP54 |
| Switch on duration | 30 |

MOUNTING POSITIONS



TECHNICAL DATA

| | |
|-------------------------------|--|
| Matchcode | PA-LSA-75/200 |
| Article name | Slit actuator PA-LSA-75/200 |
| Part number | M2 2471 A |
| Input voltage | 24 V DC |
| Nominal current | 1.1 |
| Stroke | 181 |
| Push force | 750 |
| Pull force | 750 |
| Nominal locking force | 1000 |
| Cut-Off | integrated electronic overload cut-off |
| Running speed | 7.6 |
| IP code | IP54 |
| Switch on duration | 30 |
| Mounting way | aufgesetzt |
| Weight | 1.9 |
| Housing | Aluminium profile tube, anodised E6/EV1 with integrated holder for flexible bracket system |
| Housing type | Aluminium |
| Colour | On request |
| Housing length | 535 |
| Housing height | 42 |
| Diameter | 36 |
| Appliance class | III |
| Connection cable | SICO PLUG connection. Excluding connection cable / set. |
| Nominal working temperature | 20 |
| Environment temperature range | -5 °C - 75 °C |
| Brackets included | ja |
| Customs tariff no | 84798997 |

ACCESSORIES

| Part no. | Matchcode |
|---------------------------|-----------------------------------|
| K2 1505 A | UKU-740 |
| K2 1539 | HK-L |
| K2 1563 | K-L-UK-J |
| K2 2004 | PA-ANL-3m |
| K2 2005 | PA-ANL-5m |
| K2 2006 | PA-ANL-+lfm |
| K2 2007 | PA-SICO-SET-3m |
| K2 2008 | PA-SICO-SET-5m |
| K2 2009 | PA-SICO-SET-+lfm |
| SD1 8522 | SICO-LINK-Adapter |
| SD1 8525 | SICO-PLUCKER |