


Technical Data



Input voltage	24 V DC
Nominal current	1.1
Running speed	7.6
IP code	IP54
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	PA-L-75/500-S
Article name	Linear actuator PA-L-75/500-S
Part number	M2 2413 S
Input voltage	24 V DC
Nominal current	1.1
Input voltage range	- 15 % / + 15 %
Stroke	500
Push force	750
Pull force	750
Nominal locking force	1000
Cut-Off	electronic and sequence signal "F"
Running speed	7.6
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	2.2
Housing	end-to-end aluminium profile tube, anodized in EV1
Housing type	Aluminium
Colour	On request
Housing length	887
Housing height	42
Diameter	36
Appliance class	III
Connection cable	SICO PLUG connection. Excluding connection cable / set.
Nominal working temperature	20
Environment temperature range	-5 °C - 75 °C

Brackets included
Customs tariff no

nein
84798997

ACCESSORIES

Part no.	Matchcode
K2 1501	OK
K2 1502	DAS
K2 1505 A	UKU-740
K2 1506	AW 100-6
K2 1506 A	AW 100-6-A
K2 1507 A	AW 150-6
K2 1507 B	AW 150-6-A
K2 1519 A	AW 250-6
K2 1539	HK-L
K2 1562	UK-L
K2 1563	K-L-UK-J
K2 1576	K-L-RAICO105D-RE-9006 (rechts)
K2 1577	K-L-RAICO105D-LI-9006 (links)
K2 1601	K-L-A-LI-AW57RO
K2 1603	K-L-A-RE-AW57RO
K2 2004	PA-ANL-3m
K2 2005	PA-ANL-5m
K2 2006	PA-ANL-+lfm
K2 2007	PA-SICO-SET-3m
K2 2008	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm