

Linear actuator PA-L-75/500-S

Technical Data











Input voltage 24 V DC

Nominal current 1.1 Running speed 7.6

IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-75/500-S

Article name Linear actuator PA-L-75/500-S
Part number M2 2413 S

Input voltage 24 V DC
Nominal current 1.1

Input voltage range -15 % / +15 % Networked standby -15 % / +15 %

Stroke500Push force750Pull force750Nominal locking force1000

Cut-Off electronic and sequence signal "F"

Running speed 7.6
IP code IP54
Switch on duration 30

Mounting way aufgesetzt Weight 2.2

Housing end-to-end aluminium profile tube, anodized in

EV1

Housing type Aluminium
Colour On request
Housing length 887

Housing length 88
Housing height 42
Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.

Nominal working temperature 20



Linear actuator PA-L-75/500-S

Environment temperature range Brackets included Customs tariff no -5 °C - 75 °C nein 84798997

ACCESSORIES

Part no.	Matchcode
<u>K2 1501</u>	<u>OK</u>
<u>K2 1502</u>	<u>DAS</u>
K2 1505 A	<u>UKU-740</u>
K2 1506	AW 100-6
K2 1506 A	<u>AW 100-6-A</u>
K2 1507 A	<u>AW 150-6</u>
K2 1507 B	AW 150-6-A
K2 1519 A	AW 250-6
<u>K2 1539</u>	<u>HK-L</u>
K2 1562	UK-L
K2 1563	K-L-UK-J
<u>K2 2004</u>	PA-ANL-3m
<u>K2 2005</u>	PA-ANL-5m
<u>K2 2006</u>	PA-ANL-+Ifm
<u>K2 2007</u>	PA-SICO-SET-3m
K2 2008	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER