

Linear actuator PA-L-100/300-S

Technical Data













Input voltage 24 V DC

Nominal current 1.0
Running speed 4.4
IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-100/300-S
Article name Linear actuator PA-L-100/300-S

Part number M2 2422 S

Input voltage 24 V DC
Nominal current 1.0

Input voltage range -15%/+15%Networked standby 0.9 W (1 min)Stroke 300

Stroke 300
Push force 1000
Pull force 1000
Nominal locking force 1000

Cut-Off integrated electronic overload cut-off

Running speed 4.4
IP code IP54
Switch on duration 30

Mounting way aufgesetzt Weight 1.7

Housing End-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

Housing type Aluminium
Colour On request

Housing length 687
Housing height 42
Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-100/300-S

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES	
Part no.	Matchcode
K2 1501	<u>OK</u>
K2 1502	DAS
<u>K2 1505 A</u>	<u>UKU-740</u>
K2 1506	<u>AW 100-6</u>
K2 1506 A	<u>AW 100-6-A</u>
K2 1507 A	<u>AW 150-6</u>
K2 1507 B	<u>AW 150-6-A</u>
K2 1519 A	AW 250-6
K2 1539	<u>HK-L</u>
K2 1562	<u>UK-L</u>
<u>K2 1563</u>	K-L-UK-J
<u>K2 1576</u>	K-L-RAICO105D-RE-9006 (rechts)
K2 1577	K-L-RAICO105D-LI-9006 (links)
K2 1601	K-L-A-LI-AW57RO
K2 1603	K-L-A-RE-AW57RO
K2 2004	PA-ANL-3m
<u>K2 2005</u>	PA-ANL-5m
<u>K2 2006</u>	PA-ANL-+Ifm
<u>K2 2007</u>	PA-SICO-SET-3m
<u>K2 2008</u>	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+Ifm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER