

Linear actuator PA-L-100/500-S

Technical Data











Input voltage 24 V DC Nominal current 1.0

Running speed 4.4

IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-100/500-S

Article name Linear actuator PA-L-100/500-S
Part number M2 2423 S

Input voltage 24 V DC Nominal current 1.0

Input voltage range -15 % / + 15 %

Stroke500Push force1000Pull force1000Nominal locking force1000

Cut-Off electronic and sequence signal "F"

Running speed 4.4 IP code IP54 Switch on duration 30

Mounting way aufgesetzt

Weight 2.2

Housing end-to-end aluminium profile tube, anodized in EV1

Housing type Aluminium

Colour On request
Housing length 887
Housing height 42
Diameter 36

Diameter 36
Appliance class III

Connection cable SICO PLUG connection. Excluding connection

cable / set.

20

Nominal working temperature

Environment temperature range -5 °C - 75 °C



Linear actuator PA-L-100/500-S

Brackets included Customs tariff no

ACCESSORIES

K2 1601

K2 1603

K2 2009

nein 84798997

710020011120	
Part no.	Matchcode
<u>K2 1501</u>	<u>OK</u>
<u>K2 1502</u>	<u>DAS</u>
<u>K2 1505 A</u>	<u>UKU-740</u>
<u>K2 1506</u>	AW 100-6
K2 1506 A	<u>AW 100-6-A</u>
K2 1507 A	AW 150-6
K2 1507 B	<u>AW 150-6-A</u>
K2 1519 A	<u>AW 250-6</u>
<u>K2 1539</u>	<u>HK-L</u>
<u>K2 1562</u>	<u>UK-L</u>
<u>K2 1563</u>	<u>K-L-UK-J</u>
<u>K2 1576</u>	K-L-RAICO105D-RE-9006 (rechts)
<u>K2 1577</u>	K-L-RAICO105D-LI-9006 (links)

K-L-A-LI-AW57RO K-L-A-RE-AW57RO

PA-SICO-SET-+Ifm