



Technical Data



Input voltage	24 V DC
Nominal current	1.0
Running speed	7.7
IP code	IP54
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	PA-LS-50/300-S
Article name	Slit actuator PA-LS-50/300-S
Part number	M2 2462 S
Input voltage	24 V DC
Nominal current	1.0
Input voltage range	- 15 % / + 15 %
Networked standby	0.9 W (1 min)
Stroke	281
Push force	500
Pull force	500
Nominal locking force	1000
Cut-Off	Integrated electronic overload cut-off
Running speed	7.7
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	2.1
Housing	End-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible bracket system
Housing type	Aluminium
Colour	On request
Housing length	635
Housing height	42

Diameter	36
Appliance class	III
Connection cable	SICO PLUG connection. Excluding connection cable / set.
Nominal working temperature	20
Environment temperature range	-5 °C - 75 °C
Brackets included	nein
Customs tariff no	84798997

ACCESSORIES

Part no.	Matchcode	
K2 1501	OK	
K2 1502	DAS	
K2 1505 A	UKU-740	
K2 1539	HK-L	
K2 1562	UK-L	
K2 1563	K-L-UK-J	
K2 1576	K-L-RAICO105D-RE-9006 (rechts)	
K2 1577	K-L-RAICO105D-LI-9006 (links)	
K2 1601	K-L-A-LI-AW57RO	
K2 1603	K-L-A-RE-AW57RO	
K2 2004	PA-ANL-3m	
K2 2005	PA-ANL-5m	
K2 2006	PA-ANL-+lfm	
K2 2007	PA-SICO-SET-3m	
K2 2008	PA-SICO-SET-5m	
K2 2009	PA-SICO-SET-+lfm	
SD1 8522	SICO-LINK-Adapter	
SD1 8525	SICO-PLUCKER	