



Technical Data



| | |
|--------------------|---------|
| Input voltage | 24 V DC |
| Nominal current | 1.0 |
| Running speed | 10.5 |
| IP code | IP32 |
| Switch on duration | 30 |

MOUNTING POSITIONS



TECHNICAL DATA

| | |
|-------------------------------|---|
| Matchcode | PA-K-20/1000-S |
| Article name | Chain actuator PA-K-20/1000-S |
| Part number | M2 2205 S |
| Input voltage | 24 V DC |
| Nominal current | 1.0 |
| Input voltage range | - 15 % / + 15 % |
| Stroke | 1000 |
| Push force | 200 |
| Pull force | 200 |
| Nominal locking force | ≤ 2000 |
| Cut-Off | Integrated electronic overload cut-off |
| Running speed | 10.5 |
| IP code | IP32 |
| Switch on duration | 30 |
| Mounting way | aufgesetzt |
| Weight | 1.3 |
| Housing | Aluminium profile housing EV1 anodized |
| Housing type | Aluminium |
| Colour | On request |
| Housing length | 832 |
| Housing width | 39 |
| Housing height | 24 |
| Appliance class | III |
| Connection cable | SICO PLUG connection. Excluding connection cable / set. |
| Nominal working temperature | 20 |
| Environment temperature range | -5 °C - 75 °C |
| Brackets included | nein |
| Customs tariff no | 84798997 |

ACCESSORIES

| Part no. | Matchcode |
|--------------------------|-----------------------------------|
| K2 2007 | PA-SICO-SET-3m |
| K2 2008 | PA-SICO-SET-5m |
| K2 2009 | PA-SICO-SET-+lfm |
| K2 2201 | K-K20-OK-SB |
| K2 2202 | K-K20-OK-DL |
| K2 2203 | K-K20-HK |
| K2 2204 | K-K20-AKI-SB |
| K2 2205 | K-K20-AKI-DL |
| K2 2206 | K-K20-S-SB |
| K2 2207 | K-K20-S-DL |
| SD1 8513 | SICO-LINK-USB-110 |
| SD1 8522 | SICO-LINK-Adapter |
| SD1 8525 | SICO-PLUCKER |