



## Technical Data



|                    |         |
|--------------------|---------|
| Input voltage      | 24 V DC |
| Nominal current    | 1.0     |
| Running speed      | 10.5    |
| IP code            | IP32    |
| Switch on duration | 30      |

## MOUNTING POSITIONS



## TECHNICAL DATA

|                               |   |
|-------------------------------|---|
| Matchcode                     | PA-KI-20/600-S  |
| Article name                  | Chain actuator PA-KI-20/600-S                           |
| Part number                   | M2 2208 S   |
| Input voltage                 | 24 V DC   |
| Nominal current               | 1.0   |
| Input voltage range           | - 15 % / + 15 %   |
| Stroke                        | 600   |
| Push force                    | 200   |
| Pull force                    | 200   |
| Nominal locking force         | ≤ 2000  |
| Cut-Off                       | Integrated electronic overload cut-off                  |
| Running speed                 | 10.5  |
| IP code                       | IP32  |
| Switch on duration            | 30  |
| Mounting way                  | integriert  |
| Weight                        | 1.1   |
| Housing                       | Without housing   |
| Housing type                  | Steel case  |
| Colour                        | On request  |
| Housing length                | 625   |
| Housing width                 | 35  |
| Housing height                | 20  |
| Appliance class               | III   |
| Connection cable              | SICO PLUG connection. Excluding connection cable / set. |
| Nominal working temperature   | 20  |
| Environment temperature range | -5 °C - 75 °C   |
| Brackets included             | nein  |
| Customs tariff no             | 84798997  |

**ACCESSORIES**

| Part no.                 | Matchcode                         |
|--------------------------|-----------------------------------|
| <a href="#">K2 2007</a>  | <a href="#">PA-SICO-SET-3m</a>    |
| <a href="#">K2 2008</a>  | <a href="#">PA-SICO-SET-5m</a>    |
| <a href="#">K2 2009</a>  | <a href="#">PA-SICO-SET-+lfm</a>  |
| <a href="#">K2 2201</a>  | <a href="#">K-K20-OK-SB</a>       |
| <a href="#">K2 2202</a>  | <a href="#">K-K20-OK-DL</a>       |
| <a href="#">K2 2203</a>  | <a href="#">K-K20-HK</a>          |
| <a href="#">K2 2204</a>  | <a href="#">K-K20-AKI-SB</a>      |
| <a href="#">K2 2205</a>  | <a href="#">K-K20-AKI-DL</a>      |
| <a href="#">K2 2206</a>  | <a href="#">K-K20-S-SB</a>        |
| <a href="#">K2 2207</a>  | <a href="#">K-K20-S-DL</a>        |
| <a href="#">SD1 8513</a> | <a href="#">SICO-LINK-USB-110</a> |
| <a href="#">SD1 8522</a> | <a href="#">SICO-LINK-Adapter</a> |
| <a href="#">SD1 8525</a> | <a href="#">SICO-PLUCKER</a>      |