



Technical Data



Input voltage	24 V DC
Nominal current	1.0
Running speed	10.5
IP code	IP32
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	PA-KI-20/800-S-DA
Article name	Chain actuator PA-KI-20/800-S-DA
Part number	M2 2209 S DA
Input voltage	24 V DC
Nominal current	1.0
Input voltage range	- 15 % / + 15 %
Stroke	800
Push force	200
Pull force	200
Nominal locking force	≤ 2000
Cut-Off	Integrated electronic overload cut-off
Running speed	10.5
IP code	IP32
Switch on duration	30
Mounting way	integriert
Weight	1.2
Housing	Without housing
Housing type	Steel case
Colour	On request
Housing length	729
Housing width	35
Housing height	20
Appliance class	III
Connection cable	SICO PLUG connection. Excluding connection cable / set.
Nominal working temperature	20
Environment temperature range	-5 °C - 75 °C
Brackets included	nein
Customs tariff no	84798997

ACCESSORIES

Part no.	Matchcode
K2 2007	PA-SICO-SET-3m
K2 2008	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm
K2 2201	K-K20-OK-SB
K2 2202	K-K20-OK-DL
K2 2203	K-K20-HK
K2 2204	K-K20-AKI-SB
K2 2205	K-K20-AKI-DL
K2 2206	K-K20-S-SB
K2 2207	K-K20-S-DL
SD1 8513	SICO-LINK-USB-110