



Technical Data



| | |
|--------------------|---------|
| Input voltage | 24 V DC |
| Nominal current | 1.4 |
| Switch on duration | 30 |

TECHNICAL DATA

| | |
|-------------------------------|--|
| Matchcode | PA-ZV-ELIMATIC-A |
| Article name | Supplementary electric locking PA-ZV-ELIMATIC-A |
| Part number | B5 6201 |
| Input voltage | 24 V DC |
| Nominal current | 1.4 |
| Input voltage range | - 15 % / + 15 % |
| Ripple | 500 |
| Cut-Off | build-in electronic overload cut-off |
| IP code | IP32 |
| Switch on duration | 30 |
| Mounting way | aufgesetzt |
| Weight | 0.95 |
| Housing | Aluminum E6 / EV1, anodised |
| Housing type | Aluminium |
| Housing length | 310 |
| Housing width | 50 |
| Housing height | 41 |
| Appliance class | III |
| Connection cable | SICO connection cable 3 × 0,5 mm ² or 6 × 0,5 mm ² |
| Nominal working temperature | 20 |
| Environment temperature range | 0 °C - +75 °C |

ACCESSORIES

| Part no. | Matchcode |
|-------------------------|--|
| B5 6128 | Z-ZV-ELIMATIC-Huelsenset |