

Linear actuator PA-L-90/200-S

Technical Data













24 V DC Input voltage

Nominal current 1.2 Running speed 7.6

IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-90/200-S Article name

Linear actuator PA-L-90/200-S Part number M2 2431 S

24 V DC Input voltage Nominal current 1.2

Input voltage range - 15 % / + 15 % Networked standby 0.9 W (1 min)

Stroke 200 Push force 900 Pull force 900

Nominal locking force 1000

Cut-Off integrated electronic overload cut-off

Running speed 7.6 IP code **IP54** Switch on duration 30

aufgesetzt Mounting way Weight 1.45

End-to-end aluminium profile tube, anodized in Housing E6/EV1 with integrated retainer for flexible

bracket system Housing type Aluminium Colour On request

Housing length 587 Housing height 42 36 Diameter Appliance class

Connection cable SICO PLUG connection. Excluding connection

cable / set.



Linear actuator PA-L-90/200-S

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES	
Part no.	Matchcode
K2 1501	<u>OK</u>
K2 1502	<u>DAS</u>
<u>K2 1505 A</u>	<u>UKU-740</u>
K2 1506	AW 100-6
K2 1506 A	AW 100-6-A
K2 1507 A	AW 150-6
K2 1507 B	AW 150-6-A
K2 1519 A	AW 250-6
<u>K2 1539</u>	<u>HK-L</u>
K2 1562	<u>UK-L</u>
K2 1563	<u>K-L-UK-J</u>
<u>K2 1576</u>	K-L-RAICO105D-RE-9006 (rechts)
<u>K2 1577</u>	K-L-RAICO105D-LI-9006 (links)
K2 1601	K-L-A-LI-AW57RO
K2 1603	K-L-A-RE-AW57RO
K2 2004	PA-ANL-3m
K2 2005	PA-ANL-5m
K2 2006	PA-ANL-+Ifm
<u>K2 2007</u>	PA-SICO-SET-3m
<u>K2 2008</u>	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER