

Linear actuator PA-L-90/300-S

Technical Data













Input voltage 24 V DC

Nominal current 1.2 Running speed 7.6

IP code IP54

Switch on duration 30

MOUNTING POSITIONS

























TECHNICAL DATA

Matchcode PA-L-90/300-S Article name Linear actuator

Article name Linear actuator PA-L-90/300-S
Part number M2 2432 S

Input voltage 24 V DC
Nominal current 1.2

Input voltage range - 15 % / + 15 % Networked standby 0.9 W (1 min)

Stroke 300
Push force 900
Pull force 900
Nominal locking force 1000

Nominal locking force 1000
Cut-Off integrated electronic overload cut-off

Running speed 7.6 IP code IP54

Switch on duration 30

Mounting way aufgesetzt
Weight 1.7

Housing End-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible

bracket system
Aluminium

On request

SICO PLUG connection. Excluding connection

cable / set.

Housing length
Housing height
Diameter
Appliance class
Connection cable



Linear actuator PA-L-90/300-S

Nominal working temperature Environment temperature range Brackets included Customs tariff no 20 -5 °C - 75 °C nein 84798997

ACCESSORIES	
Part no.	Matchcode
K2 1501	<u>OK</u>
<u>K2 1502</u>	<u>DAS</u>
<u>K2 1505 A</u>	<u>UKU-740</u>
<u>K2 1506</u>	<u>AW 100-6</u>
K2 1506 A	<u>AW 100-6-A</u>
K2 1507 A	AW 150-6
K2 1507 B	AW 150-6-A
K2 1519 A	AW 250-6
K2 1539	HK-L
K2 1562	<u>UK-L</u>
K2 1563	<u>K-L-UK-J</u>
<u>K2 1576</u>	K-L-RAICO105D-RE-9006 (rechts)
<u>K2 1577</u>	K-L-RAICO105D-LI-9006 (links)
K2 1601	K-L-A-LI-AW57RO
K2 1603	K-L-A-RE-AW57RO
K2 2004	PA-ANL-3m
K2 2005	PA-ANL-5m
K2 2006	PA-ANL-+Ifm
K2 2007	PA-SICO-SET-3m
<u>K2 2008</u>	PA-SICO-SET-5m
K2 2009	PA-SICO-SET-+lfm
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER