



Technical Data



| | |
|--------------------|---------|
| Input voltage | 24 V DC |
| Nominal current | 0.095 |
| Switch on duration | 30 |

TECHNICAL DATA

| | |
|-------------------------------|---|
| Matchcode | PA-ZV-UNI2 |
| Article name | Supplementary electric locking PA-ZV-UNI2 |
| Part number | B5 6231 |
| Input voltage | 24 V DC |
| Nominal current | 0.095 |
| Input voltage range | +/- 15% |
| Ripple | 500 |
| Push force | 200 |
| Nominal locking force | 750 |
| Cut-Off | - integrated electronic overload cut-off - Overload protection: electronic - Max. switching current of all sequence actuators: 6 A - Switching time sequence control: approx. 2 seconds. Attention: no actuator is activated during this time |
| IP code | IP40 |
| Switch on duration | 30 |
| Mounting way | aufgesetzt |
| Weight | 0.9 |
| Housing | Aluminum E6 / EV1 |
| Housing type | Aluminium |
| Colour | RAL & DB colors |
| Housing length | 385 |
| Housing width | 25 |
| Housing height | 35 |
| Appliance class | III |
| Connection cable | SICO PLUG connection |
| Nominal working temperature | 20 |
| Environment temperature range | 0 °C - 75 °C |
| Brackets included | ja |