



## Technical Data



|                    |         |
|--------------------|---------|
| Input voltage      | 24 V DC |
| Nominal current    | 1.0     |
| Running speed      | 7.7     |
| IP code            | IP20    |
| Switch on duration | 30      |

## MOUNTING POSITIONS



## TECHNICAL DATA

|                               |                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------|
| Matchcode                     | PA-LSL-75/48-TG24-RE                                                                       |
| Article name                  | Louvre slit actuator PA-LSL-75/48-TG24-RE                                                  |
| Part number                   | M2 2482                                                                                    |
| Input voltage                 | 24 V DC                                                                                    |
| Nominal current               | 1.0                                                                                        |
| Stroke                        | 48                                                                                         |
| Push force                    | 750                                                                                        |
| Pull force                    | 750                                                                                        |
| Nominal locking force         | 1000                                                                                       |
| Cut-Off                       | integrated electronic overload cut-off                                                     |
| Running speed                 | 7.7                                                                                        |
| IP code                       | IP20                                                                                       |
| Switch on duration            | 30                                                                                         |
| Mounting way                  | aufgesetzt                                                                                 |
| Weight                        | 1.75                                                                                       |
| Housing                       | Aluminium profile tube, anodised E6/EV1 with integrated holder for flexible bracket system |
| Housing type                  | Aluminium                                                                                  |
| Colour                        | On request                                                                                 |
| Housing length                | 427                                                                                        |
| Housing height                | 42                                                                                         |
| Diameter                      | 36                                                                                         |
| Appliance class               | III                                                                                        |
| Connection cable              | SICO PLUG connection. Excluding connection cable / set.                                    |
| Nominal working temperature   | 20                                                                                         |
| Environment temperature range | -5 °C - 75 °C                                                                              |
| Brackets included             | ja                                                                                         |
| Customs tariff no             | 84798997                                                                                   |

## ACCESSORIES

| Part no.                  | Matchcode                         |  |
|---------------------------|-----------------------------------|--|
| <a href="#">K2 1505 A</a> | <a href="#">UKU-740</a>           |  |
| <a href="#">K2 1539</a>   | <a href="#">HK-L</a>              |  |
| <a href="#">K2 1563</a>   | <a href="#">K-L-UK-J</a>          |  |
| <a href="#">K2 2004</a>   | <a href="#">PA-ANL-3m</a>         |  |
| <a href="#">K2 2005</a>   | <a href="#">PA-ANL-5m</a>         |  |
| <a href="#">K2 2006</a>   | <a href="#">PA-ANL-+lfm</a>       |  |
| <a href="#">K2 2007</a>   | <a href="#">PA-SICO-SET-3m</a>    |  |
| <a href="#">K2 2008</a>   | <a href="#">PA-SICO-SET-5m</a>    |  |
| <a href="#">K2 2009</a>   | <a href="#">PA-SICO-SET-+lfm</a>  |  |
| <a href="#">SD1 8522</a>  | <a href="#">SICO-LINK-Adapter</a> |  |
| <a href="#">SD1 8525</a>  | <a href="#">SICO-PLUCKER</a>      |  |